according to Regulation (EC) No 1907/2006

## **Durolan Thinner**

Revision date: 30.05.2022 Page 1 of 11

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

**Durolan Thinner** 

Product code:

25010

UFI: U4H3-G01M-800P-K3KQ

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Coatings and paints, thinners, paint removers Reserved for industrial and professional use.

# 1.3. Details of the supplier of the safety data sheet

Company name: DFS-DIAMON GmbH

Street: Ländenstr. 1

Place: D-93339 Riedenburg

Telephone: +49 (0)9442 9189 0 Telefax: +49 (0)9442 9189 37

e-mail: info@dfs-diamon.de Contact person: Armin Aunkofer

e-mail: armin.aunkofer@dfs-diamon.de

Internet: www.dfs-diamon.de

**1.4. Emergency telephone** 24 hour Emergency Contact: +49 (0) 700 24112112 (DFS)

<u>number:</u> +1 872 5888271

## **SECTION 2: Hazards identification**

# 2.1. Classification of the substance or mixture

# Regulation (EC) No 1272/2008

Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

### 2.2. Label elements

# Regulation (EC) No 1272/2008

# Hazard components for labelling

ethyl acetate

acetone; propan-2-one; propanone propan-2-ol; isopropyl alcohol; isopropanol

Signal word: Danger

Pictograms:





# **Hazard statements**

H225 Highly flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

#### **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

Print date: 30.05.2022

# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

## **Durolan Thinner**

Revision date: 30.05.2022 Page 2 of 11

smoking.

P233 Keep container tightly closed.

P280 Wear protective gloves and eye/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P403+P235 Store in a well-ventilated place. Keep cool.

## Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

## 2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## **SECTION 3: Composition/information on ingredients**

## 3.2. Mixtures

## **Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
141-78-6	ethyl acetate			35 - < 40 %
	205-500-4	607-022-00-5		
	Flam. Liq. 2, Eye Irrit. 2, STOT S	E 3; H225 H319 H336 EUH06	6	
67-64-1	acetone; propan-2-one; propanone			35 - < 40 %
	200-662-2	606-001-00-8	01-2119471330-49	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			20 - < 25 %
	200-661-7	603-117-00-0	01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
108-65-6	2-methoxy-1-methylethyl acetate			10 - < 15 %
	203-603-9	607-195-00-7	01-2119475791-29	
	Flam. Liq. 3; H226			

Full text of H and EUH statements: see section 16.

# **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

#### **General information**

When in doubt or if symptoms are observed, get medical advice.

# After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. If experiencing respiratory symptoms: Call a doctor.

## After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off contaminated clothing and wash it before reuse. In case of skin reactions, consult a physician.

# After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately. Remove contact lenses, if present and easy to do. Continue rinsing.

according to Regulation (EC) No 1907/2006

#### **Durolan Thinner**

Revision date: 30.05.2022 Page 3 of 11

#### After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person or a person with cramps. Seek medical advice immediately.

#### 4.2. Most important symptoms and effects, both acute and delayed

No information available.

# 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

# **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

### Suitable extinguishing media

Water spray jet, Carbon dioxide (CO2), alcohol resistant foam, Extinguishing powder.

Co-ordinate fire-fighting measures to the fire surroundings.

## Unsuitable extinguishing media

High power water jet.

## 5.2. Special hazards arising from the substance or mixture

Highly flammable. Vapours are heavier than air, spread along floors and form explosive mixtures with air. In case of fire may be liberated: Carbon monoxide, Carbon dioxide (CO2), Pyrolysis products, toxic.

#### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Full protection suit.

#### Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

# **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

## General advice

Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Evacuate area.

# For non-emergency personnel

Remove all sources of ignition. Provide adequate ventilation. Use personal protection equipment.

## For emergency responders

Use personal protection equipment.

# 6.2. Environmental precautions

Do not allow to enter into surface water or drains. Danger of explosion

# 6.3. Methods and material for containment and cleaning up

#### For containment

Stop leak if safe to do so. Cover drains.

#### For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Ventilate affected area.

## Other information

Use non-sparking tools.

Clean contaminated articles and floor according to the environmental legislation.

#### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

according to Regulation (EC) No 1907/2006

#### **Durolan Thinner**

Revision date: 30.05.2022 Page 4 of 11

Disposal: see section 13

# **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

## Advice on safe handling

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

# Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours are heavier than air, spread along floors and form explosive mixtures with air.

# Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

#### Further information on handling

Never use pressure to empty container.

## 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

## Hints on joint storage

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances. Strong acid, Strong alkali.

# Further information on storage conditions

Keep away from heat. Protect from direct sunlight.

storage temperature: 15 - 30°C

# 7.3. Specific end use(s)

Coatings and paints, thinners, paint removers Reserved for industrial and professional use.

# **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

## Occupational exposure limits

Substance	ppm	mg/m³	fib/cm³	Category	Origin
2-Methoxy-1-methylethylacetate	50	275		TWA (8 h)	
	100	550		STEL (15 min)	
Acetone	500	1210		TWA (8 h)	
Ethyl acetate	200	734		TWA (8 h)	
	400	1468		STEL (15 min)	
Isopropyl alcohol	200	-		TWA (8 h)	
	400	-		STEL (15 min)	
	2-Methoxy-1-methylethylacetate  Acetone  Ethyl acetate	2-Methoxy-1-methylethylacetate 50 100 Acetone 500 Ethyl acetate 200 400 Isopropyl alcohol 200	2-Methoxy-1-methylethylacetate 50 275 100 550 Acetone 500 1210 Ethyl acetate 200 734 400 1468	2-Methoxy-1-methylethylacetate 50 275 100 550 Acetone 500 1210 Ethyl acetate 200 734 400 1468 Isopropyl alcohol 200 -	2-Methoxy-1-methylethylacetate 50 275 TWA (8 h) 100 550 STEL (15 min) Acetone 500 1210 TWA (8 h) Ethyl acetate 200 734 TWA (8 h) STEL (15 min) 1468 STEL (15 min) Isopropyl alcohol 200 - TWA (8 h)

according to Regulation (EC) No 1907/2006

## **Durolan Thinner**

Revision date: 30.05.2022 Page 5 of 11

## **Biological limit values**

CAS No	Substance	Parameter	Value	Test material	Sampling time
67-64-1	Acetone	Acetone	50 mg/L	Urine	End of shift
67-63-0	2-Propanol	Acetone	40 mg/L	-	End of shift at end of workweek

#### **DNEL/DMEL values**

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			
Worker DNEL, long-term		dermal	systemic	888 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	500 mg/m³

#### **PNEC values**

CAS No	Substance		
Environmental compartment Value		Value	
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol		
Freshwater		140,9 mg/l	
Freshwater (	intermittent releases)	140,9 mg/l	
Marine water		140,9 mg/l	
Marine sediment		552 mg/kg	
Micro-organisms in sewage treatment plants (STP)		2251 mg/l	
Soil		28 mg/kg	

# 8.2. Exposure controls









## Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

# Individual protection measures, such as personal protective equipment

# Eye/face protection

Use eye protection according to EN 166. Tightly sealed safety glasses.

## Hand protection

Wear suitable gloves tested to EN374.

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

# Skin protection

Wear suitable protective clothing.

## Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Respiratory protection necessary at: exceeding exposure limit values

according to Regulation (EC) No 1907/2006

## **Durolan Thinner**

Revision date: 30.05.2022 Page 6 of 11

#### Thermal hazards

Flame-retardant protective clothing. Wear anti-static footwear and clothing

## **Environmental exposure controls**

Avoid release to the environment.

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: colourless
Odour: characteristic
Odour threshold: not determined

# Changes in the physical state

Melting point/freezing point: not determined
Boiling point or initial boiling point and (Acetone) 56 °C

boiling range:

Flash point: - 18 °C

**Flammability** 

Solid/liquid: not applicable
Gas: not applicable

Lower explosion limits:

Upper explosion limits:

1,5 vol. %

12,8 vol. %

Auto-ignition temperature:

Decomposition temperature:

not determined pH-Value:

not determined viscosity / kinematic:

National physical physi

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined

Vapour pressure: 96.4 hPa

(at 20 °C)

Density (at 20 °C): 1 g/cm³
Relative vapour density: not determined
Particle characteristics: not applicable

# 9.2. Other information

# Other safety characteristics

Danger of explosion: Vapours can form explosive mixtures with air.

Dynamic viscosity (20°C): 0,5 mPa\*s

# **SECTION 10: Stability and reactivity**

# 10.1. Reactivity

Highly flammable.

# 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

# 10.3. Possibility of hazardous reactions

according to Regulation (EC) No 1907/2006

#### **Durolan Thinner**

Revision date: 30.05.2022 Page 7 of 11

Vapours can form explosive mixtures with air.

Exothermic reaction with: Strong acid, Strong alkali, Oxidizing agents, strong.

#### 10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Keep away from heat. Protect from direct sunlight.

# 10.5. Incompatible materials

Oxidising agent. Pyrophoric or self-heating substances. Strong acid, Strong alkali

## 10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide, Carbon dioxide (CO2), Pyrolysis products, toxic.

## **SECTION 11: Toxicological information**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Based on available data, the classification criteria are not met.

#### Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

#### Sensitising effects

Based on available data, the classification criteria are not met.

## Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

#### STOT-single exposure

May cause drowsiness or dizziness. (ethyl acetate; acetone; propan-2-one; propanone; propan-2-ol; isopropyl alcohol; isopropanol)

# STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

# **Aspiration hazard**

Based on available data, the classification criteria are not met.

### Information on likely routes of exposure

oral, Skin contact, Eye contact, Inhalation.

#### 11.2. Information on other hazards

#### **Endocrine disrupting properties**

No information available.

## **SECTION 12: Ecological information**

## 12.1. Toxicity

The product is not: Ecotoxic.

# 12.2. Persistence and degradability

The product has not been tested.

## 12.3. Bioaccumulative potential

The product has not been tested.

### 12.4. Mobility in soil

The product has not been tested.

## 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

according to Regulation (EC) No 1907/2006

## **Durolan Thinner**

Revision date: 30.05.2022 Page 8 of 11

## 12.7. Other adverse effects

No information available.

#### **Further information**

Avoid release to the environment.

# **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

## **Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

#### Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

# **SECTION 14: Transport information**

# Land transport (ADR/RID)

14.1. UN number or ID number: UN 1263

14.2. UN proper shipping name: PAINT RELATED MATERIAL

14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Classification code: F1

Special Provisions: 163 367 640D 650

Limited quantity: 5 L
Excepted quantity: E2
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1263

14.2. UN proper shipping name: Paint related material

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Classification code: F1

Special Provisions: 163 367 640D 650

Limited quantity: 5 L Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 1263

14.2. UN proper shipping name: PAINT RELATED MATERIAL

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3

according to Regulation (EC) No 1907/2006

## **Durolan Thinner**

Revision date: 30.05.2022 Page 9 of 11



Marine pollutant:

Special Provisions: 163, 367
Limited quantity: 5 L
Excepted quantity: E2
EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1263

14.2. UN proper shipping name: PAINT RELATED MATERIAL

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Special Provisions: A3 A72 A192

Limited quantity Passenger: 1 L
Passenger LQ: Y341
Excepted quantity: E2

IATA-packing instructions - Passenger:353IATA-max. quantity - Passenger:5 LIATA-packing instructions - Cargo:364IATA-max. quantity - Cargo:60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

## 14.6. Special precautions for user

Warning: flammable liquids. Vapours can form explosive mixtures with air.

# 14.7. Maritime transport in bulk according to IMO instruments

not applicable

# **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

2010/75/EU (VOC): 100 %

Information according to 2012/18/EU P5c FLAMMABLE LIQUIDS

(SEVESO III):

**National regulatory information** 

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

# 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

## **SECTION 16: Other information**

## Changes

according to Regulation (EC) No 1907/2006

#### **Durolan Thinner**

Revision date: 30.05.2022 Page 10 of 11

This data sheet contains changes from the previous version in section(s): 1,2,4,5,6,7,8,9,10,11,12,13,14,15,16.

## Abbreviations and acronyms

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

**UN: United Nations** 

CAS: Chemical Abstracts Service
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate LC50: Lethal concentration, 50%

LD50: Lethal dose, 50% LL50: Lethal loading, 50% EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate

NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic vPvB: very persistent, very bioaccumulative

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Regulations concerning the international carriage of dangerous goods by rail

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

IMDG: International Maritime Code for Dangerous Goods

EmS: Emergency Schedules MFAG: Medical First Aid Guide

IATA: International Air Transport Association ICAO: International Civil Aviation Organization

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container VOC: Volatile Organic Compounds SVHC: Substance of Very High Concern

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

## Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure			
Flam. Liq. 2; H225	On basis of test data			
Eye Irrit. 2; H319	Calculation method			
STOT SE 3; H336	Calculation method			

# Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

## **Further Information**

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

according to Regulation (EC) No 1907/2006

# **Durolan Thinner**

Revision date: 30.05.2022 Page 11 of 11

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)