

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Cold model hardener

Revision date: 10.03.2020

Product code: 167-215

Page 1 of 9

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Cold model hardener

#### Further trade names

Article No.: 167-215-00

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Use of the substance/mixture

Health services.

#### 1.3. Details of the supplier of the safety data sheet

Company name:	DENTAURUM GmbH & Co. KG	
Street:	Turnstr. 31	
Place:	D-75228 Ispringen	
Telephone:	+49 7231 803 0	Telefax: +49 7231 803 295
e-mail:	info@dentaurum.de	
Internet:	www.dentaurum.com	

#### Further Information

Emergency telephone:  
 07:00 - 16:15 (Mo - Do), 07:00 - 13:15 (Fr) +49 7231 803 184  
 16:15 - 18:00 (Mo - Do), 13:15 - 18:00 (Fr) +49 7231 803 0

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Regulation (EC) No. 1272/2008

Hazard categories:  
 Flammable liquid: Flam. Liq. 2  
 Specific target organ toxicity - single exposure: STOT SE 3  
 Hazard Statements:  
 Highly flammable liquid and vapour.  
 May cause drowsiness or dizziness.

#### 2.2. Label elements

##### Regulation (EC) No. 1272/2008

##### Hazard components for labelling

n-butyl acetate

Signal word: Danger

##### Pictograms:



##### Hazard statements

H225 Highly flammable liquid and vapour.  
 H336 May cause drowsiness or dizziness.

##### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P240 Ground and bond container and receiving equipment.  
 P243 Take action to prevent static discharges.  
 P271 Use only outdoors or in a well-ventilated area.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Cold model hardener**

Revision date: 10.03.2020

Product code: 167-215

Page 2 of 9

P370+P378

In case of fire: Use Carbon dioxide (CO<sub>2</sub>), Foam, Extinguishing powder to extinguish.**2.3. Other hazards**

No information available.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Chemical characterization**

Synthetic resin in butylacetate

**Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
123-86-4	n-butyl acetate			45-55 %
	204-658-1	607-025-00-1		
	Flam. Liq. 3, STOT SE 3; H226 H336 EUH066			
64-17-5	ethanol; ethyl alcohol			3-7 %
	200-578-6	603-002-00-5		
	Flam. Liq. 2; H225			

Full text of H and EUH statements: see section 16.

**SECTION 4: First aid measures****4.1. Description of first aid measures****After inhalation**

Provide fresh air. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

**After contact with skin**

Wash with plenty of water. Take off contaminated clothing and wash it before reuse.

**After contact with eyes**

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist.

**After ingestion**

Rinse mouth immediately and drink plenty of water. Have victim drink large quantities of water, with active charcoal if possible. Do NOT induce vomiting.

**4.2. Most important symptoms and effects, both acute and delayed**

No information available.

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**Carbon dioxide (CO<sub>2</sub>), Foam, Extinguishing powder.**Unsuitable extinguishing media**

Water.

**5.2. Special hazards arising from the substance or mixture**

Flammable. Vapours can form explosive mixtures with air.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Cold model hardener

Revision date: 10.03.2020

Product code: 167-215

Page 3 of 9

#### **5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

#### **Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

### **SECTION 6: Accidental release measures**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

Remove all sources of ignition. Avoid contact with skin, eyes and clothes. Use personal protection equipment. Do not breathe vapour.

#### **6.2. Environmental precautions**

Do not allow uncontrolled discharge of product into the environment. Danger of explosion

#### **6.3. Methods and material for containment and cleaning up**

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

#### **6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

### **SECTION 7: Handling and storage**

#### **7.1. Precautions for safe handling**

##### **Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe vapour.

##### **Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

#### **7.2. Conditions for safe storage, including any incompatibilities**

##### **Requirements for storage rooms and vessels**

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not store at temperatures over: 30°C

##### **Hints on joint storage**

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

#### **7.3. Specific end use(s)**

Health services.

### **SECTION 8: Exposure controls/personal protection**

#### **8.1. Control parameters**

##### **Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
123-86-4	Butyl acetate	150	724		TWA (8 h)	WEL
		200	966		STEL (15 min)	WEL
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL

#### **8.2. Exposure controls**

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Cold model hardener**

Revision date: 10.03.2020

Product code: 167-215

Page 4 of 9

**Appropriate engineering controls**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe vapour.

**Protective and hygiene measures**

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.  
Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

**Eye/face protection**

Wear eye protection/face protection.

**Hand protection**

Recommendation:

Dermatril Single-use gloves. NBR (Nitrile rubber). 0,11 mm penetration time (maximum wearing period): 0 min.  
REF 162-907-00 (7/S), REF 162-908-00 (8/M), REF 162-909-00 (9/L)

-----  
Camapren 720, CR (polychloroprenes, Chloroprene rubber). 0,65 mm penetration time (maximum wearing period): 10 min, KCL

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

**Skin protection**

Flame-retardant protective clothing. Wear anti-static footwear and clothing

**Respiratory protection**

In case of inadequate ventilation wear respiratory protection. Respiratory protection necessary at: aerosol or mist generation.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state:	liquid
Colour:	brown, transparent
Odour:	fruity
pH-Value:	not determined
<b>Changes in the physical state</b>	
Melting point:	-77 °C
Initial boiling point and boiling range:	126 °C
Flash point:	19 °C
<b>Flammability</b>	
Solid:	not applicable
Gas:	not applicable
Lower explosion limits:	1,2 vol. %
Upper explosion limits:	7,5 vol. %
Ignition temperature:	370 °C

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Cold model hardener**

Revision date: 10.03.2020

Product code: 167-215

Page 5 of 9

**Auto-ignition temperature**

Solid: not applicable  
 Gas: not applicable

Decomposition temperature: not determined

**Oxidizing properties**

Not oxidising.

Vapour pressure: 13 hPa  
 (at 20 °C)

Density (at 20 °C): 0,95 g/cm<sup>3</sup>

Water solubility: The study does not need to be conducted  
 because the substance is known to be  
 insoluble in water.

**Solubility in other solvents**

not determined

Partition coefficient: not determined

Vapour density: not determined

Evaporation rate: not determined

**9.2. Other information**

Solid content: not determined

**SECTION 10: Stability and reactivity****10.1. Reactivity**

Flammable, Ignition hazard.

**10.2. Chemical stability**

The product is stable under storage at normal ambient temperatures.

**10.3. Possibility of hazardous reactions**

Reacts with : Alkali metals. Alkalis (alkalis). Oxidizing agents.  
 Vapours may form explosive mixtures with air.

**10.4. Conditions to avoid**

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

**10.5. Incompatible materials**

No information available.

**10.6. Hazardous decomposition products**

Acetic acid.

**SECTION 11: Toxicological information****11.1. Information on toxicological effects****Acute toxicity**

Based on available data, the classification criteria are not met.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Cold model hardener

Revision date: 10.03.2020

Product code: 167-215

Page 6 of 9

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64-17-5	ethanol; ethyl alcohol				
	oral	LD50 mg/kg	6200	Rat	IUCLID
	inhalation (4 h) vapour	LC50	95,6 mg/l	Rat	RTECS

#### **Irritation and corrosivity**

Irritant effect on the eye: irritant.

#### **Sensitising effects**

Based on available data, the classification criteria are not met.

#### **Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

#### **STOT-single exposure**

May cause drowsiness or dizziness. (n-butyl acetate)

#### **STOT-repeated exposure**

Based on available data, the classification criteria are not met.

#### **Aspiration hazard**

Based on available data, the classification criteria are not met.

#### **Specific effects in experiment on an animal**

none

#### **Additional information on tests**

none

## SECTION 12: Ecological information

### **12.1. Toxicity**

Toxic to fish.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
123-86-4	n-butyl acetate					
	Acute fish toxicity	LC50	62 mg/l	96 h	Leuciscus idus (golden orfe)	
64-17-5	ethanol; ethyl alcohol					
	Acute crustacea toxicity	EC50	9268 - 14221 mg/l	48 h	Daphnia magna	IUCLID

### **12.2. Persistence and degradability**

The product has not been tested.

### **12.3. Bioaccumulative potential**

The product has not been tested.

### **Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
64-17-5	ethanol; ethyl alcohol	-0,31

### **12.4. Mobility in soil**

The product has not been tested.

### **12.5. Results of PBT and vPvB assessment**

The product has not been tested.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

**Cold model hardener**

Revision date: 10.03.2020

Product code: 167-215

Page 7 of 9

**12.6. Other adverse effects**

No information available.

**Further information**

Avoid release to the environment.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation. Send to a hazardous waste incinerator facility under observation of official regulations .

**List of Wastes Code - used product**

140603 WASTE ORGANIC SOLVENTS, REFRIGERANTS AND PROPELLANTS (EXCEPT 07 AND 08); waste organic solvents, refrigerants and foam/aerosol propellants; other solvents and solvent mixtures; hazardous waste

**Contaminated packaging**

Wash with plenty of water. Completely emptied packages can be recycled.

**SECTION 14: Transport information****Land transport (ADR/RID)**

<b>14.1. UN number:</b>	UN 1866
<b>14.2. UN proper shipping name:</b>	Resin solution
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3



Classification code:	F1
Special Provisions:	640D
Limited quantity:	5 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	33
Tunnel restriction code:	D/E

**Marine transport (IMDG)**

<b>14.1. UN number:</b>	UN 1866
<b>14.2. UN proper shipping name:</b>	Resin solution
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3



Special Provisions:	-
Limited quantity:	5 L
Excepted quantity:	E2
EmS:	F-E, S-E

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006


**Cold model hardener**

Revision date: 10.03.2020

Product code: 167-215

Page 8 of 9

**Air transport (ICAO-TI/IATA-DGR)**

<b>14.1. UN number:</b>	UN 1866
<b>14.2. UN proper shipping name:</b>	Resin solution
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3
	
Special Provisions:	A3
Limited quantity Passenger:	1 L
Passenger LQ:	Y341
Excepted quantity:	E2
IATA-packing instructions - Passenger:	353
IATA-max. quantity - Passenger:	5 L
IATA-packing instructions - Cargo:	364
IATA-max. quantity - Cargo:	60 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: no

**14.6. Special precautions for user**

Warning: Combustible liquid.

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

not applicable

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

2010/75/EU (VOC):	4 % (38 g/l)
2004/42/EC (VOC):	4 % (38 g/l)

**Additional information**

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC

**National regulatory information**

Employment restrictions:	Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).
Water hazard class (D):	1 - slightly hazardous to water

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information****Abbreviations and acronyms**

ADR: Accord européen sur le transport des marchandises dangereuses par Route  
(European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances



**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Cold model hardener**

Revision date: 10.03.2020

Product code: 167-215

Page 9 of 9

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

**Relevant H and EUH statements (number and full text)**

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*