

## Safety Data Sheet according to Regulation (EU) 2020/878

Date of issue: 30.07.2021  
Revision date: -  
Effective from: 30.07.2021  
Version: 1

Replaced version: -

Pro-Die Spacer  
Pro-Die Hardener  
Pro-Seal wax sealing

### **SECTION 1: Identification of the substance/mixture and of the company/undertaking**

#### **1.1. Product identifier**

Substance name/ Trade name: Ethyl acetate / Die Spacers + Die Hardener / Pro-Seal wax sealing  
03-2000, 03-2040, 03-2060, 03-2070, 03-2090, 03-2100 //03-2020 /03-1980// 03-2300  
EC index no: 607-002-00-5  
EC no: 205-500-4  
CAS no: 141-78-6  
REACH registration no: 01-2119475103-46-xxxx

#### **1.2. Relevant identified uses of the substance or mixture and uses advised against**

Relevant identified uses:  
SU 20 Healthcare. Plaster die seal or wax seal for use in the dental laboratory  
Uses advised against:  
Do not use outside of the dental laboratory.

#### **1.3. Details of the supplier of the safety data sheet**

**Manufacturer/Supplier**  
al dente Dentalprodukte GmbH

**Street / mailbox:**  
Borsigstr. 1

**Country code / postal code / city:**  
D-38644 Goslar

**Contact for technical information**  
+49 (0) 5321-80031

**Phone / Fax / E-mail**  
+49 (0)5321-80031 / +49 (0)5321-50881 / E-Mail: info@aldente.de

#### **1.4. Emergency telephone number**

+49 (0) 171 8637790

### **SECTION 2: Hazards identification**

#### **2.1. Classification of the substance or mixture**

**Classification according to Regulation (EC) No. 1272/2008 [CLP]**  
Flammable liquids, Category 2, H225  
Serious eye damage/eye irritation, Category 2, H319  
Specific target organ toxicity — Single exposure, Category 3, Narcosis, H336

Full text of H statements: see section 16.

#### **Adverse physicochemical, human health and environmental effects**

Highly flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizziness.

## Safety Data Sheet according to Regulation (EU) 2020/878

Date of issue: 30.07.2021  
Revision date: -  
Effective from: 30.07.2021  
Version: 1

Pro-Die Spacer  
Pro-Die Hardener  
Pro-Seal wax sealing

Replaced version: -

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Signal word (CLP) : Danger

Hazard statements (CLP) : H225 - Highly flammable liquid and vapour  
H319 - Causes serious eye irritation  
H336 - May cause drowsiness or dizziness

Precautionary statements (CLP) : P233 - Keep container tightly closed  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
P102 - Keep out of reach of children  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

EUH phrases : EUH066 - Repeated exposure may cause skin dryness or cracking

### 2.3. Other hazards

Results of PBT and vPvB assessment:

PBT: Not applicable.

vPvB: Not applicable.

## **SECTION 3: Composition/information on ingredients**

### 3.1. Substances

Main constituent of the substance:

Name: Ethyl acetate

EC index no: 607-002-00-5

EC no: 205-500-4

CAS no: 141-78-6

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Ethyl acetate	(CAS no) 141-78-6 (EC no) 205-500-4 (EC index no) 607-022-00-5 (REACH no) 01-2119475103-46-xxxx	≤ 100	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

Full text of H statements: see section 16.

Impurities, stabilizing additives and individual constituents:

Name: Solution of binders and auxiliary materials, depending on the Die Spacer Type color pigments

EC index no: not applicable

EC no: not applicable

CAS no: not applicable

### 3.2. Mixtures

Not applicable

## **SECTION 4: First aid measures**

## Safety Data Sheet according to Regulation (EU) 2020/878

Date of issue: 30.07.2021  
Revision date: -  
Effective from: 30.07.2021  
Version: 1

Replaced version: -

Pro-Die Spacer  
Pro-Die Hardener  
Pro-Seal wax sealing

### 4.1. Description of first aid measures

**General measures:** Call a doctor if you feel unwell. If possible show him this sheet. Failing this, show him the packaging or label. Never give anything by mouth to an unconscious person. Place the affected person in the recovery position.

**After inhalation:** Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.

**After skin contact:** Take off contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.

**After eye contact:** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

**After ingestion:** Rinse mouth. Drink water as a precaution. Do NOT induce vomiting.

### 4.2. Most important symptoms and effects, both acute and delayed

**Symptoms/injuries after inhalation:** May cause drowsiness or dizziness.

**Symptoms/injuries after eye contact:** Causes serious eye irritation.

**Other symptoms/injuries:** Nausea, vomiting, headache, drooling.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

Suitable extinguishing media: Dry extinguishing powder. Foam. Carbon dioxide.  
Unsuitable extinguishing media: Water.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard: Highly flammable liquid and vapour.  
Explosion hazard: May form flammable/explosive vapour-air mixture.  
Hazardous decomposition products in case of fire: Toxic fumes may be released. Carbon monoxide. Carbon dioxide.

### 5.3. Advice for firefighters

Protection during firefighting: Use a self-contained breathing apparatus and also a protective suit.

## **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures: Stop leak if safe to do so. Provide adequate ventilation. Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking. Avoid contact with skin and eyes. Do not breathe vapour/aerosol.

For non-emergency personnel:

Emergency procedures: Evacuate unnecessary personnel.

For emergency responders:

Protective equipment: Wear personal protective equipment. Use self-contained breathing apparatus.

### 6.2. Environmental precautions

## Safety Data Sheet according to Regulation (EU) 2020/878

Date of issue: 30.07.2021  
Revision date: -  
Effective from: 30.07.2021  
Version: 1

Replaced version: -

Pro-Die Spacer  
Pro-Die Hardener  
Pro-Seal wax sealing

Prevent entry to sewers and public waters.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Dispose of in accordance with relevant local regulations.

### 6.4. Reference to other sections

Exposure controls and personal protection, see section 8. Concerning disposal elimination after cleaning, see section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed: Handle empty containers with care because residual vapours are flammable.

Precautions for safe handling: Provide good ventilation in process area to prevent formation of vapour. Remove ignition sources. No open flames. No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Wear personal protective clothing. Do not breathe vapour/aerosol. Avoid contact with skin and eyes.

Hygiene measures: Handle in accordance with good industrial hygiene and safety procedures. When using do not eat, drink or smoke. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Take off contaminated clothing and wash it before reuse. Contaminated work clothing should not be allowed out of the workplace.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures: Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting equipment.

Storage temperature: < 30 °C

Storage conditions: Store in original container. Keep container tightly closed. Store in a cool, well-ventilated place. Protect from sunlight. Keep in fireproof place. Store locked up. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Prohibitions on mixed storage: Keep away from food, drink and animal feedingstuffs.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Ethyl acetate (141-78-6)		
EU	Local name	Ethyl acetate
EU	IOELV TWA (mg/m <sup>3</sup> )	734 mg/m <sup>3</sup>
EU	IOELV TWA (ppm)	200 ppm
EU	IOELV STEL (mg/m <sup>3</sup> )	1468 mg/m <sup>3</sup>
EU	IOELV STEL (ppm)	400 ppm
Ireland	Local name	Ethyl acetate
Ireland	OEL (8 hours ref) (ppm)	200 ppm
Ireland	OEL (8 hours ref) (mg/m <sup>3</sup> )	734 mg/m <sup>3</sup>
Ireland	OEL (15 min ref) (ppm)	400 ppm
Ireland	OEL (15 min ref) (mg/m <sup>3</sup> )	1468 mg/m <sup>3</sup>
Ireland	Notes	IOELV

## Safety Data Sheet according to Regulation (EU) 2020/878

Date of issue: 30.07.2021  
Revision date: -  
Effective from: 30.07.2021  
Version: 1

Pro-Die Spacer  
Pro-Die Hardener  
Pro-Seal wax sealing

Replaced version: -

<b>Ethyl acetate (141-78-6)</b>		
Malta	Local name	Ethyl acetate
Malta	OEL 8 hours (mg/m <sup>3</sup> )	734 mg/m <sup>3</sup>
Malta	OEL 8 hours (ppm)	200 ppm
Malta	OEL STEL (mg/m <sup>3</sup> )	1468 mg/m <sup>3</sup>
Malta	OEL STEL (ppm)	400 ppm
United Kingdom	Local name	Ethyl acetate
United Kingdom	WEL TWA (ppm)	200 ppm
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	734 mg/m <sup>3</sup>
United Kingdom	WEL STEL (ppm)	400 ppm
United Kingdom	WEL STEL (mg/m <sup>3</sup> )	1468 mg/m <sup>3</sup>
<b>Ethyl acetate (141-78-6)</b>		
<b>DNEL/DMEL (Workers)</b>		
Acute - systemic effects, inhalation	1468 mg/m <sup>3</sup>	
Acute - local effects, inhalation	1468 mg/m <sup>3</sup>	
Long-term - systemic effects, inhalation	734 mg/m <sup>3</sup>	
Long-term - local effects, inhalation	734 mg/m <sup>3</sup>	
Long-term - systemic effects, dermal	63 mg/kg bodyweight/day	
<b>DNEL/DMEL (General population)</b>		
Acute - systemic effects, inhalation	734 mg/m <sup>3</sup>	
Acute - local effects, inhalation	734 mg/m <sup>3</sup>	
Long-term - systemic effects, oral	4.5 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	367 mg/m <sup>3</sup>	
Long-term - systemic effects, dermal	37 mg/kg bodyweight/day	
Long-term - local effects, inhalation	367 mg/m <sup>3</sup>	
<b>PNEC (Water)</b>		
PNEC aqua (freshwater)	0.24 mg/l	
PNEC aqua (marine water)	0.024 mg/l	
PNEC aqua (intermittent, freshwater)	1.65 mg/l	
<b>PNEC (Sediment)</b>		
PNEC sediment (freshwater)	1.15 mg/kg dwt	
PNEC sediment (marine water)	0.115 mg/kg dwt	
<b>PNEC (Soil)</b>		
PNEC soil	0.148 mg/kg dwt	
<b>PNEC (Oral)</b>		
PNEC oral (secondary poisoning)	200 mg/kg food	
<b>PNEC (STP)</b>		
PNEC sewage treatment plant	650 mg/l	

### 8.2. Exposure controls

Appropriate engineering controls: Provide local exhaust or general room ventilation to minimize vapour concentrations.

Hand protection: Wear suitable gloves (EN 374). Butyl rubber,  $\geq 0.7$  mm. The exact breakthrough time has to be found out by the manufacturer of the protective gloves and has to be observed. Penetration time (min.):  $\geq 60$  min

Eye protection: Wear safety glasses (EN 166).

Skin and body protection: Wear suitable protective clothing. Flame retardant antistatic protective clothing.

Respiratory protection: Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. Breathing apparatus with filter type A.

## Safety Data Sheet according to Regulation (EU) 2020/878

Date of issue: 30.07.2021  
Revision date: -  
Effective from: 30.07.2021  
Version: 1

Replaced version: -

Pro-Die Spacer  
Pro-Die Hardener  
Pro-Seal wax sealing

Environmental exposure controls: Avoid release to the environment.

### **SECTION 9: Physical and chemical properties**

#### **9.1. Information on basic physical and chemical properties**

Physical state : Liquid  
Colour : Transparent or colored according to the Die Spacer Type  
Odour : Characteristic; Odour threshold: 0.1 - 181.5 ppm  
Melting point/freezing point : -83 °C  
Boiling point or initial boiling point and boiling range : 75-77 °C  
Flammability : Highly flammable liquid and vapour.  
Lower and upper explosion limit : 2.1 – 11.5 vol.-%  
Flash point : -4 °C  
Auto-ignition temperature : 460 °C  
Decomposition temperature : No data available  
pH : No data available  
Kinematic viscosity : No data available  
Solubility : Water: 79 g/l  
Partition coefficient n-octanol/water (log value) : 0.68 (25 °C)  
Vapour pressure : No data available  
Density and/or relative density : No data available  
Relative vapour density : No data available  
Particle characteristics : Not applicable

#### **9.2. Other information**

Explosive properties : May form flammable/explosive vapour-air mixture.

### **SECTION 10: Stability and reactivity**

#### **10.1. Reactivity**

Highly flammable liquid and vapour. May form flammable/explosive vapour-air mixture.

#### **10.2. Chemical stability**

Stable under use and storage conditions as recommended in section 7.

#### **10.3. Possibility of hazardous reactions**

The substance can react with strong oxidizing agents.

#### **10.4. Conditions to avoid**

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition. Prolonged storage above 45 °C.

#### **10.5. Incompatible materials**

Strong oxidizing agents.

#### **10.6. Hazardous decomposition products**

No hazardous decomposition products known. In case of fire: Toxic fumes may be released. Carbon dioxide. Carbon monoxide.

### **SECTION 11: Toxicological information**

#### **11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

## Safety Data Sheet according to Regulation (EU) 2020/878

Date of issue: 30.07.2021  
Revision date: -  
Effective from: 30.07.2021  
Version: 1

Pro-Die Spacer  
Pro-Die Hardener  
Pro-Seal wax sealing

Replaced version: -

Acute toxicity : Not classified  
Based on available data, the classification criteria are not met

<b>Ethyl acetate (141-78-6)</b>	
LD50 oral rabbit	4934 mg/kg
LD50 dermal rabbit	> 20000 mg/kg
LC50 inhalation rat (Vapours)	> 22.5 mg/l/6 h

Skin corrosion/irritation : Not classified  
Based on available data, the classification criteria are not met

Serious eye damage/irritation : Causes serious eye irritation

Respiratory or skin sensitisation : Not classified  
Based on available data, the classification criteria are not met

Germ cell mutagenicity : Not classified  
Based on available data, the classification criteria are not met

Carcinogenicity : Not classified  
Based on available data, the classification criteria are not met

Reproductive toxicity : Not classified  
Based on available data, the classification criteria are not met

Specific target organ toxicity (single exposure) : May cause drowsiness or dizziness

Specific target organ toxicity (repeated exposure) : Not classified  
Based on available data, the classification criteria are not met

Aspiration hazard : Not classified  
Based on available data, the classification criteria are not met

### 11.2. Information on other hazards

Potential adverse human health effects and symptoms : Based on available data, the classification criteria are not met

## **SECTION 12: Ecological information**

### 12.1. Toxicity

Acute aquatic toxicity : Not classified  
Chronic aquatic toxicity : Not classified

<b>Ethyl acetate (141-78-6)</b>	
LC50 fish	230 mg/l 96 h, Pimephales promelas
EC50 Daphnia	165 mg/l Daphnia Cucullata
EC50 microorganisms	5870 mg/l 15 min, Photobacterium phosphoreum
NOEC algae	> 100 mg/l 72 h, Desmodesmus subspicatus

### 12.2. Persistence and degradability

<b>Ethyl acetate (141-78-6)</b>	
Persistence and degradability	Readily biodegradable.
Biodegradation	69 %, 15 d

### 12.3. Bioaccumulative potential

<b>Ethyl acetate (141-78-6)</b>	
Partition coefficient n-octanol/water (Log Pow)	0.68 (25 °C)
Bioaccumulative potential	Bioaccumulation unlikely.

## Safety Data Sheet according to Regulation (EU) 2020/878

Date of issue: 30.07.2021  
Revision date: -  
Effective from: 30.07.2021  
Version: 1

Replaced version: -

Pro-Die Spacer  
Pro-Die Hardener  
Pro-Seal wax sealing

### 12.4. Mobility in soil

No additional information available.

### 12.5. Results of PBT and vPvB assessment

This substance does not meet the PBT- or vPvB criteria of REACH regulation, annex XIII.

### 12.6. Endocrine disrupting properties

No additional information available.

### 12.7. Other adverse effects

No additional information available.

## **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

#### **Regional legislation (waste)**

Dispose in a safe manner in accordance with local/national regulations. The product is to be classified as hazardous waste (waste paints).

#### **Waste treatment methods**

This material and its container must be disposed of in a safe way.

#### **Waste disposal recommendations**

Treat contaminated packaging like the product itself.

#### **Waste code**

The waste code number according to the Ordinance on the European Waste Catalogue (AVV) depends on the waste producer and can therefore vary for any given product. The waste code number is therefore to be gleaned separately from each waste producer.

#### **Additional information**

Handle empty containers with care because residual vapours are flammable. Depending on the use. Do not perforate, cut or weld uncleaned containers.

## **SECTION 14: Transport information**

In accordance with ADR / IMDG / IATA

### 14.1. UN number or ID number

UN-No. (ADR) : UN 1173  
UN-No. (IMDG) : UN 1173  
UN-No. (IATA) : UN 1173

### 14.2. UN proper shipping name

Proper Shipping Name (ADR) : ETHYL ACETATE  
Proper Shipping Name (IMDG) : ETHYL ACETATE  
Proper Shipping Name (IATA) : Ethyl acetate  
Transport document description (ADR) : UN 1173 ETHYL ACETATE, 3, II, (D/E)  
Transport document description (IMDG) : UN 1173 ETHYL ACETATE, 3, II



## Safety Data Sheet according to Regulation (EU) 2020/878

**Date of issue:** 30.07.2021  
**Revision date:** -  
**Effective from:** 30.07.2021  
**Version:** 1

Pro-Die Spacer  
Pro-Die Hardener  
Pro-Seal wax sealing

**Replaced version:** -

Transport document description (IATA) : UN 1173 Ethyl acetate, 3, II

### 14.3. Transport hazard class(es)

#### ADR

Transport hazard class(es) (ADR) : 3  
Danger labels (ADR) : 3



#### IMDG

Transport hazard class(es) (IMDG) : 3  
Danger labels (IMDG) : 3



#### IATA

Transport hazard class(es) (IATA) : 3  
Hazard labels (IATA) : 3



### 14.4. Packing group

Packing group (ADR) : II  
Packing group (IMDG) : II  
Packing group (IATA) : II

### 14.5. Environmental hazards

Dangerous for the environment : No  
Marine pollutant : No  
Other information : No supplementary information available

### 14.6. Special precautions for user

#### - Overland transport

Classification code (ADR) : F1  
Limited quantities (ADR) : 1L  
Excepted quantities (ADR) : E2  
Packing instructions (ADR) : P001, IBC02, R001  
Mixed packing provisions (ADR) : MP19  
Portable tank and bulk container instructions (ADR) : T4

## Safety Data Sheet according to Regulation (EU) 2020/878

Date of issue: 30.07.2021  
Revision date: -  
Effective from: 30.07.2021  
Version: 1

Pro-Die Spacer  
Pro-Die Hardener  
Pro-Seal wax sealing

Replaced version: -

Portable tank and bulk container special provisions (ADR) : TP1  
Tank code (ADR) : LGBF  
Vehicle for tank carriage : FL  
Transport category (ADR) : 2  
Special provisions for carriage - Operation (ADR) : S2, S20  
Hazard identification number (Kemler No.) : 33  
Orange plates :



Tunnel restriction code (ADR) : D/E  
**- Transport by sea**  
Limited quantities (IMDG) : 1 L  
Excepted quantities (IMDG) : E2  
Packing instructions (IMDG) : P001  
IBC packing instructions (IMDG) : IBC02  
Tank instructions (IMDG) : T4  
Tank special provisions (IMDG) : TP1  
EmS-No. (Fire) : F-E  
EmS-No. (Spillage) : S-D  
Stowage category (IMDG) : B  
Flash point (IMDG) : -4°C c.c.

**- Air transport**  
PCA Excepted quantities (IATA) : E2  
PCA Limited quantities (IATA) : Y341  
PCA limited quantity max net quantity (IATA) : 1L  
PCA packing instructions (IATA) : 353  
PCA max net quantity (IATA) : 5L  
CAO packing instructions (IATA) : 364  
CAO max net quantity (IATA) : 60L  
ERG code (IATA) : 3L

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## **SECTION 15: Regulatory information**

### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

EU-Regulations:  
Ethyl acetate is not on the REACH Annex XIV List  
Ethyl acetate is not on the REACH Candidate List

## Safety Data Sheet according to Regulation (EU) 2020/878

**Date of issue:** 30.07.2021  
**Revision date:** -  
**Effective from:** 30.07.2021  
**Version:** 1

Pro-Die Spacer  
Pro-Die Hardener  
Pro-Seal wax sealing

**Replaced version:** -

Ethyl acetate is not subject to Regulation (EU) No. 649/2012 of the European Parliament and of the Council of July 4, 2012 concerning the export and import of hazardous chemicals  
Ethyl acetate is not subject to Regulation (EU) No. 2019/1021 of the European Parliament and of the Council of June 20, 2019 on persistent organic pollutants  
Does not contain any substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of June 20, 2019 on the marketing and use of explosives precursors  
Ethyl acetate is not subject to Regulation (EC) No. 1005/2009 of the European Parliament and of the Council of September 16, 2009 on substances that deplete the ozone layer  
Ethyl acetate is not subject to Regulation (EC) No. 648/2004 of the European Parliament and of the Council of March 31, 2004 on detergents

National regulations:  
No additional information available

### 15.2. Chemical safety assessment

For this substance, a chemical safety assessment was not carried out.

## **SECTION 16: Other information**

### **Changes compared to earlier versions**

-

### **Data source**

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006

### **Abbreviations and acronyms:**

ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road  
CLP : Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures  
DMEL : Derived Minimal Effect Level  
DNEL : Derived No-Effect Level  
EC50 : The effective concentration of substance that causes 50% of the maximum response (Median Effective Concentration)  
IATA : International Air Transport Association  
IMDG : "International Maritime Dangerous Goods Code" for the transport of dangerous goods by sea  
LC50 : Lethal Concentration to 50 % of a test population (Median Lethal Concentration)  
LD50 : Lethal Dose to 50% of a test population (Median Lethal Dose)  
LOAEL : No Observed Effect Concentration/Level  
NOAEC/L : Organisation for Economic Cooperation and Development  
NOEC/L : Persistent, Bioaccumulative and Toxic substance  
OECD : Predicted No-Effect Concentration  
PBT : Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals  
PNEC : Safety Data Sheet  
REACH : Sewage Treatment Plant  
SDB (SDS) : Unique Formula Identifier  
STP : Very Persistent and Very Bioaccumulative  
UFI : European Agreement concerning the International Carriage of Dangerous Goods by Road  
vPvB : Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

### **Full text of H- and EUH-statements:**

## Safety Data Sheet according to Regulation (EU) 2020/878

**Date of issue:** 30.07.2021

**Revision date:** -

**Effective from:** 30.07.2021

**Version:** 1

**Replaced version:** -

Pro-Die Spacer

Pro-Die Hardener

Pro-Seal wax sealing

---

Eye Irrit. 2 : Serious eye damage/eye irritation, Category 2  
Flam. Liq. 2 : Flammable liquids, Category 2  
STOT SE 3 : Specific target organ toxicity - Single exposure, Category 3, Narcosis  
H225 : Highly flammable liquid and vapour  
H319 : Causes serious eye irritation  
H336 : May cause drowsiness or dizziness  
EUH066 : Repeated exposure may cause skin dryness or cracking

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.