

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Telescan Spray white/red (flammable)

Revision date: 11.01.2023

Page 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Telescan Spray white/red (flammable)

Product code:

11166, 11167, 11168, 11169

UFI:

YRE3-90QG-P00T-2J8W

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Restricted to professional users.

1.3. Details of the supplier of the safety data sheet

Company name:	DFS-DIAMON GmbH	
Street:	Ländenstr. 1	
Place:	D-93339 Riedenburg	
Telephone:	+49 (0)9442 9189 0	Telefax: +49 (0)9442 9189 37
e-mail:	info@dfs-diamon.de	
Contact person:	Armin Aunkofer	
e-mail:	armin.aunkofer@dfs-diamon.de	
Internet:	www.dfs-diamon.de	

1.4. Emergency telephone number:

24 hour Emergency Contact: +49 (0) 700 24112112 (DFS)
+1 872 5888271

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008Aerosol 1; H222-H229
Eye Irrit. 2; H319
STOT SE 3; H336
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008**Hazard components for labelling**pentane
isopentane; 2-methylbutane**Signal word:** Danger**Pictograms:****Hazard statements**

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Telescan Spray white/red (flammable)

Revision date: 11.01.2023

Page 2 of 14

Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Special labelling of certain mixtures

- EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Telescan Spray white/red (flammable)

Revision date: 11.01.2023

Page 3 of 14

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
106-97-8	butane			20 - 45 %
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1, Compressed gas; H220 H280			
75-28-5	isobutane			20 - 45 %
	200-857-2	601-004-00-0	01-2119485395-27	
	Flam. Gas 1, Compressed gas; H220 H280			
74-98-6	propane			20 - 45 %
	200-827-9	601-003-00-5	01-2119474691-32	
	Flam. Gas 1, Compressed gas; H220 H280			
115-07-1	propene; propylene			< 20 %
	204-062-1	601-011-00-9	01-2119447103-50	
	Flam. Gas 1, Compressed gas; H220 H280			
25167-67-3	Butene, Isomeres			< 20 %
	246-689-3			
	Flam. Gas 1A, Compressed gas; H220 H280			
13463-67-7	titanium dioxide			5 - < 10 %
	236-675-5	022-006-00-2	01-2119489379-17	
	Carc. 2; H351			
109-66-0	pentane			1 - < 5 %
	203-692-4	601-006-00-1	01-2119459286-30	
	Flam. Liq. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H336 H304 H411 EUH066			
64-17-5	ethanol, ethyl alcohol			1 - < 5 %
	200-578-6	603-002-00-5	01-2119457610-43	
	Flam. Liq. 2, Eye Irrit. 2; H225 H319			
78-78-4	isopentane; 2-methylbutane			1 - < 5 %
	201-142-8	601-085-00-2	01-2119475602-38	
	Flam. Liq. 1, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H224 H336 H304 H411 EUH066			
78-93-3	butanone; ethyl methyl ketone			< 1 %
	201-159-0	606-002-00-3	01-2119457290-43	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
13463-67-7	236-675-5	titanium dioxide	5 - < 10 %
	inhalation: LC50 = > 6,82 mg/l (dusts or mists); oral: LD50 = > 10000 mg/kg		
64-17-5	200-578-6	ethanol, ethyl alcohol	1 - < 5 %
	inhalation: LC50 = 124,7 mg/l (vapours); oral: LD50 = 10470 mg/kg		
78-93-3	201-159-0	butanone; ethyl methyl ketone	< 1 %
	inhalation: LC50 = 10000 mg/l (vapours); dermal: LD50 = 5000 mg/kg; oral: LD50 = 3300 mg/kg		

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Telescan Spray white/red (flammable)

Revision date: 11.01.2023

Page 4 of 14

Further Information

Titanium dioxide: Classification according to Regulation (EC) No 1272/2008 [CLP] 14. ATP: Note W, Note 10

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice.

After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. If experiencing respiratory symptoms: Call a doctor.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In case of skin reactions, consult a physician.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Observe risk of aspiration if vomiting occurs. If swallowed, rinse mouth with water (only if the person is conscious). Immediately call a doctor.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂), Foam, Extinguishing powder.
Co-ordinate fire-fighting measures to the fire surroundings.

5.2. Special hazards arising from the substance or mixture

Extremely flammable aerosol. Pressurized container: May burst if heated. Vapours can form explosive mixtures with air.

In case of fire may be liberated: Pyrolysis products, toxic.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Full protective suit.
Fight fire remotely due to the risk of explosion.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Evacuate area.

For non-emergency personnel

Remove all sources of ignition. Provide adequate ventilation. Use personal protection equipment.

For emergency responders

Use personal protection equipment.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Telescan Spray white/red (flammable)

Revision date: 11.01.2023

Page 5 of 14

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Explosion risk.

6.3. Methods and material for containment and cleaning up

For containment

Stop leak if safe to do so.

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Collect in closed and suitable containers for disposal.

Ventilate affected area.

Other information

Use only antistatically equipped (spark-free) tools.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

Advice on protection against fire and explosion

Do not spray on naked flames or any incandescent material. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff.

Further information on handling

Do not pierce or burn, even after use.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaust at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances. Hazardous substances that release flammable gases when in contact with water. Peroxides, flammable liquids. Other potentially explosive hazardous substances.

Further information on storage conditions

Keep away from heat. Protect from sunlight.

7.3. Specific end use(s)

Restricted to professional users.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Telescan Spray white/red (flammable)

Revision date: 11.01.2023

Page 6 of 14

Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
74-84-0	Aliphatic hydrocarbon gases, Alkanes (C1-C3), Ethane	-	-	-	Asphyxiant	
74-98-6	Aliphatic hydrocarbon gases, Alkanes (C1-C3), Propane	-	-	-	Asphyxiant	
75-28-5	Butane, all isomers - Isobutane	1000	-	-	STEL (15 min)	
106-97-8	Butane, all isomers - n-butane	1000	-	-	STEL (15 min)	
25167-67-3	Butene, mixture of isomers	250	-	-	TWA (8 h)	
64-17-5	Ethanol	1000	-	-	STEL (15 min)	
78-78-4	iso-Pentane	1000	-	-	TWA (8 h)	
78-93-3	Methyl ethyl ketone (MEK) (Butan-2-one)	200	600	-	TWA (8 h)	
		300	900	-	STEL (15 min)	
109-66-0	n-Pentane	1000	-	-	TWA (8 h)	
115-07-1	Propylene	500	-	-	TWA (8 h)	
13463-67-7	Titanium dioxide, respirable dust	-	4	-	TWA (8 h)	
13463-67-7	Titanium dioxide, total inhalable dust	-	10	-	TWA (8 h)	

Biological limit values

CAS No	Substance	Parameter	Value	Test material	Sampling time
78-93-3	Butan-2-one	Butan-2-one	70 µmol/L	Urine	Post shift

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
13463-67-7	titanium dioxide			
Worker DNEL, long-term		inhalation	local	10 mg/m ³
Consumer DNEL, long-term		oral	systemic	700 mg/kg bw/day
109-66-0	pentane			
Worker DNEL, long-term		inhalation	systemic	3000 mg/m ³
Worker DNEL, long-term		dermal	systemic	432 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	643 mg/m ³
Consumer DNEL, long-term		dermal	systemic	214 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	214 mg/kg bw/day
64-17-5	ethanol, ethyl alcohol			
Worker DNEL, long-term		inhalation	systemic	950 mg/m ³
Worker DNEL, acute		inhalation	local	1900 mg/m ³
Worker DNEL, long-term		dermal	systemic	343 mg/kg bw/day

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Telescan Spray white/red (flammable)

Revision date: 11.01.2023

Page 7 of 14

PNEC values

CAS No	Substance	Value
Environmental compartment		
13463-67-7	titanium dioxide	
Freshwater		1 mg/l
Marine water		0,127 mg/l
Freshwater sediment		1000 mg/kg
Marine sediment		100 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/kg
Soil		100 mg/kg
109-66-0	pentane	
Freshwater		0,23 mg/l
Freshwater (intermittent releases)		0,88 mg/l
Marine water		0,23 mg/l
Freshwater sediment		1,2 mg/kg
Marine sediment		1,2 mg/kg
Soil		0,55 mg/kg
64-17-5	ethanol, ethyl alcohol	
Freshwater		0,96 mg/l
Marine water		0,79 mg/l
Freshwater sediment		3,6 mg/kg
Micro-organisms in sewage treatment plants (STP)		580 mg/l
Soil		0,63 mg/kg
78-93-3	butanone; ethyl methyl ketone	
Freshwater		55,8 mg/l
Marine water		55,8 mg/l
Freshwater sediment		284,7 mg/kg
Marine sediment		284,7 mg/kg
Soil		22,5 mg/kg

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Use eye protection according to EN 166.

Hand protection

Wear suitable gloves tested to EN374.

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Telescan Spray white/red (flammable)

Revision date: 11.01.2023

Page 8 of 14

recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Respiratory protection necessary at: exceeding exposure limit values.

Thermal hazards

Flame-retardant protective clothing. Wear anti-static footwear and clothing

Environmental exposure controls

Avoid release to the environment.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid (Aerosol)
Colour:	red / white
Odour:	characteristic
Odour threshold:	not determined

Changes in the physical state

Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	(Propellant) - 42 °C
Flash point:	not determined

Flammability

Solid/liquid:	not applicable
Gas:	not applicable
Lower explosion limits:	1,4 vol. %
Upper explosion limits:	9,4 vol. %
Auto-ignition temperature:	365 °C
Decomposition temperature:	not determined
pH-Value:	not determined
Viscosity / kinematic:	not determined
Water solubility:	practically insoluble
Solubility in other solvents	not determined
Partition coefficient n-octanol/water:	not determined
Vapour pressure: (at 20 °C)	(Propellant) 8327 hPa
Vapour pressure: (at 50 °C)	(Propellant) 17081 hPa
Density:	not determined
Relative vapour density:	not determined
Particle characteristics:	not determined

9.2. Other information**Other safety characteristics**

Solid content:	5 - 10 %
----------------	----------

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Telescan Spray white/red (flammable)

Revision date: 11.01.2023

Page 9 of 14

Further Information

Explosive properties: Heating may cause an explosion. Vapours can form explosive mixtures with air.

SECTION 10: Stability and reactivity**10.1. Reactivity**

Extremely flammable aerosol. Pressurized container: May burst if heated.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Vapours can form explosive mixtures with air.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. heat. UV-radiation/sunlight.

10.5. Incompatible materials

Oxidizing agent. Pyrophoric or self-heating substances. Hazardous substances that release flammable gases when in contact with water. Peroxides, flammable liquids. Other potentially explosive hazardous substances.

10.6. Hazardous decomposition products

In case of fire may be liberated: Pyrolysis products, toxic.

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
13463-67-7	titanium dioxide				
	oral	LD50 > 10000 mg/kg	Rat	Manufacturer	
	inhalation (4 h) dust/mist	LC50 > 6,82 mg/l	Rat	Manufacturer	
64-17-5	ethanol, ethyl alcohol				
	oral	LD50 10470 mg/kg	Rat	Manufacturer	OECD 403
	inhalation (4 h) vapour	LC50 124,7 mg/l	Rat	Manufacturer	OECD 401
78-93-3	butanone; ethyl methyl ketone				
	oral	LD50 3300 mg/kg	Rat	Manufacturer	
	dermal	LD50 5000 mg/kg	Rabbit	Manufacturer	
	inhalation (4 h) vapour	LC50 10000 mg/l	Rat	Manufacturer	

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Telescan Spray white/red (flammable)

Revision date: 11.01.2023

Page 10 of 14

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

Eye contact, Skin contact, Inhalation.

Active agent: oral

11.2. Information on other hazards**Endocrine disrupting properties**

No information available.

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
13463-67-7	titanium dioxide					
	Acute fish toxicity	LC50 > 100 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	Manufacturer	OECD 203
	Acute crustacea toxicity	EC50 > 100 mg/l	48 h	Daphnia magna (Big water flea)	Manufacturer	OECD 202
64-17-5	ethanol, ethyl alcohol					
	Acute algae toxicity	ErC50 675 mg/l	96 h	Chlorella vulgaris	Manufacturer	OECD 201
	Acute crustacea toxicity	EC50 5012 mg/l	48 h	Ceriodaphnia dubia	Manufacturer	ASTM E729-80
	Fish toxicity	NOEC 250 mg/l	4 d	Danio rerio (zebrafish)	Manufacturer	OECD 212
78-93-3	butanone; ethyl methyl ketone					
	Acute fish toxicity	LC50 3220 mg/l	96 h	Pimephales promelas (fathead minnow)	Manufacturer	
	Acute crustacea toxicity	EC50 > 100 mg/l	48 h	Daphnia magna (Big water flea)	Manufacturer	

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
106-97-8	butane	2,89
64-17-5	ethanol, ethyl alcohol	-0,77

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Telescan Spray white/red (flammable)

Revision date: 11.01.2023

Page 11 of 14

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Contaminated packaging

Do not pierce or burn, even after use. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2
14.4. Packing group:	-
Hazard label:	2.1



Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	E0
Transport category:	2
Tunnel restriction code:	D

Inland waterways transport (ADN)

14.1. UN number or ID number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2
14.4. Packing group:	-
Hazard label:	2.1



Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	E0

Marine transport (IMDG)

14.1. UN number or ID number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2.1
14.4. Packing group:	-
Hazard label:	2.1

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Telescan Spray white/red (flammable)

Revision date: 11.01.2023

Page 12 of 14



Marine pollutant: -
 Special Provisions: 63, 190, 277, 327, 344, 381, 959
 Limited quantity: 1000 mL
 Excepted quantity: E0
 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS, FLAMMABLE
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
 Hazard label: 2.1



Special Provisions: A145 A167 A802
 Limited quantity Passenger: 30 kg G
 Passenger LQ: Y203
 Excepted quantity: E0
 IATA-packing instructions - Passenger: 203
 IATA-max. quantity - Passenger: 75 kg
 IATA-packing instructions - Cargo: 203
 IATA-max. quantity - Cargo: 150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Flammable gases.

Pressurised container: May burst if heated. Vapours can form explosive mixtures with air.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

2010/75/EU (VOC): < 90 %

2004/42/EC (VOC): < 90 %

Information according to 2012/18/EU (SEVESO III): P3a FLAMMABLE AEROSOLS

Additional information

Aerosol Directive (75/324/).

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Telescan Spray white/red (flammable)

Revision date: 11.01.2023

Page 13 of 14

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s):
1,2,3,4,5,6,7,8,9,10,11,12,13,14,15,16.

Abbreviations and acronyms

CLP: Classification, labelling and Packaging
 REACH: Registration, Evaluation and Authorization of Chemicals
 GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
 UN: United Nations
 CAS: Chemical Abstracts Service
 DNEL: Derived No Effect Level
 DMEL: Derived Minimal Effect Level
 PNEC: Predicted No Effect Concentration
 ATE: Acute toxicity estimate
 LC50: Lethal concentration, 50%
 LD50: Lethal dose, 50%
 LL50: Lethal loading, 50%
 EL50: Effect loading, 50%
 EC50: Effective Concentration 50%
 ErC50: Effective Concentration 50%, growth rate
 NOEC: No Observed Effect Concentration
 BCF: Bio-concentration factor
 PBT: persistent, bioaccumulative, toxic
 vPvB: very persistent, very bioaccumulative
 ADR: Accord européen sur le transport des marchandises dangereuses par Route
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 RID: Regulations concerning the international carriage of dangerous goods by rail
 ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation
 intérieures)
 IMDG: International Maritime Code for Dangerous Goods
 EmS: Emergency Schedules
 MFAG: Medical First Aid Guide
 IATA: International Air Transport Association
 ICAO: International Civil Aviation Organization
 MARPOL: International Convention for the Prevention of Marine Pollution from Ships
 IBC: Intermediate Bulk Container
 VOC: Volatile Organic Compounds
 SVHC: Substance of Very High Concern
 For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety
 assessment, chapter R.20 (Table of terms and abbreviations).

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Eye Irrit. 2; H319	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H220 Extremely flammable gas.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Telescan Spray white/red (flammable)

Revision date: 11.01.2023

Page 14 of 14

H222	Extremely flammable aerosol.
H224	Extremely flammable liquid and vapour.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)